

Trade name: MARABU-DECORLACK ACRYL Status: 01.01.2005

Product no.: 1130 Version: 2 / GB Date of printing: 12.01.2005

1.) Identification of the substance/preparation and company

Product details

Trade name

MARABU-DECORLACK ACRYL

Identification of the manufacturer / supplier

Address

Marabuwerke GmbH & Co KG

Asperger Straße 4 D-71732 Tamm

Telephone no. (++49)-7141/691-0

Fax no. (++49)-7141/691-117

Information provided by / telephone

Product safety +49 7141/691-116 or 232

Emergency telephone number

Product safety +49 7141/691-116 or 232

Use

Hobby varnish

2.) Composition / information on ingredients

Chemical characterization

Hobby varnish based on acrylic resins and on water

Hazardous ingredients

(2-METHOXYMETHYLETHOXY)PROPANOL

CAS no. 34590-94-8 EINECS no. 252-104-2

Concentration \Rightarrow 1 < 5 %-b.w.

Ink shades 004; 031 and 032 contain additionally:

ETHANE-1,2-DIOL

CAS no. 107-21-1 EINECS no. 203-473-3

Concentration \Rightarrow 1 < 5 %-b.w.

Classification Xn;R22

Ink shade 100 contains additionally: 3-BUTOXYPROPAN-2-OL

CAS no. 5131-66-8

EINECS no. 225-878-4

Concentration \Rightarrow 1 < 5 %-b.w.

Classification Xi;R36/38

3.) Hazards possibilities

4.) First aid measures

After skin contact

Wash away with soap and water and rinse. Do NOT use solvents or thinners!



Trade name: MARABU-DECORLACK ACRYL Status: 01.01.2005

Product no.: 1130 Version: 2 / GB Date of printing: 12.01.2005

After eye contact

Flush with plenty of water (10 - 15 min.).

After ingestion

Call a physician.

5.) Fire-fighting measures

Suitable extinguishing media

Carbon dioxide, foam, sand, water.

Special exposure hazards arising from the substance or preparation itself, its combustion products or from resulting gases

Material supports the burning only after evaporation of the watery content.

6.) Accidental release measures

Personal precautions

No particular measures required.

Environmental precautions

No particular measures required.

Methods for cleaning up/taking up

Wash off exhausted ink with cleaning cloths. Wash away or put into household refuse.

7.) Handling and storage

Handling

Advice on safe handling

none

Advice on protection against fire and explosion

Material supports the burning only after evaporation of the watery content.

Storage

Requirements for storage rooms and vessels

Store in frostfree conditions. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

8.) Exposure controls / personal protection

Additional hints on technical system design.

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.



Trade name: MARABU-DECORLACK ACRYL Status: 01.01.2005

Product no.: 1130 Version: 2 / GB Date of printing: 12.01.2005

Ingredients with occupational exposure limits to be monitored lnk shades 004; 031 and 032 contain additionally:

ETHANE-1,2-DIOL

2000/39/EC 20 52 Value ml/m³ mg/m³ STEL 40 ml/m³ 104 mg/m³ Skin resorption / skin sensibilisation OES/EH40 Vapour Value 52 mg/m³ **STEL** 104 mg/m³ Skin resorption / Sk sensibilisation OFS/FH40 Dust Value 10 mg/m³ OES/EH40 particulate Value 10 mg/m³ Skin resorption / Sk sensibilisation

(2-METHOXYMETHYLETHOXY)PROPANOL

2000/39/EC

Value 50 ml/m³ 308 mg/m³

Skin resorption / skin

sensibilisation

9.) Physical and chemical properties

Appearance

Form liquid coloured Odour neutral

Safety data

Changes in physical state

Type Boiling point
Value 100 °C
Reference substance (water)

Flash point

Value not applicable

Ignition temperature

Value not applicable

Explosion limits

Remarks not applicable

Vapour pressure

Value 23 hPa
Reference temperature 20 °C
Reference substance (water)

Density

Value 1,0 - 1,2 g/cm³ Reference temperature 20 °C

pH value

Value 9 - 10
Reference temperature 20 °C



Trade name: MARABU-DECORLACK ACRYL Status: 01.01.2005

Product no.: 1130 Version: 2 / GB Date of printing: 12.01.2005

10.) Stability and reactivity

Conditions to avoid

None known.

Materials to avoid

None known.

Hazardous decomposition products

None, if handled according to order.

11.) <u>Toxicological information</u>

Experience in practice

Provided all the recommended protective and safety precautions are taken, experience shows that no risk to health can be expected. Potentially serious effects, due to the residual content of solvent: Splashes in the eyes may cause mild irritation and cause the eyelids to stick together.

If swallowed, stomach complaints and irritation of the digestive organs may result.

Other information

There are no data available on the preparation itself.

The product was classified in toxicological terms on the basis of the results of the calculation procedure outlined within General Directive on Preparations (1999/45/EEC).

12.) Ecological information

General information / ecology

There are no data available on the preparation itself.

13.) <u>Disposal considerations</u>

Product

The product can be placed with other household refuse. Small residues in containers can be washedout with water and put into the drainage system.

Uncontaminated packaging

Uncleaned packaging must be disposed of in the same manner as the medium.

Completely emptied containers can be used in the recycling chain with glass or tinplate.

14.) <u>Transport information</u>

Land transport ADR/RID

Remarks non-dangerous goods

Marine transport IMDG/GGVSee

Remarks The product does not constitute a hazardous substance in sea

transport.

Air transport ICAO/IATA

Remarks The product does not constitute a hazardous substance in air transport.

15.) Regulatory information

Labelling in accordance with EC directives

The product does not require a hazard warning label in accordance with EC directives/ GefStoffV (German regulations on dangerous substances).



Trade name: MARABU-DECORLACK ACRYL Status: 01.01.2005

Product no.: 1130 Version: 2 / GB Date of printing: 12.01.2005

16.) Other information

Other information

According to their chemical structure, the applied raw materials do not contain any antimony, arsenic, soluble barium, lead, cadmium, chromium, mercury and selenium.

Product conforms therefore to DIN EN 71, part 3.

ETHANE-1,2-DIOL

22 Harmful if swallowed.

3-BUTOXYPROPAN-2-OL

36/38 Irritating to eyes and skin.

Department issuing safety data sheet

Laboratory/product safety.

Contact person

Dipl.-Chem. G. Heller or Dipl.-Ing. U. Voetter.

The instructions are based on today's information and knowledge. The safety data sheet describes products in relation to safety requirements. These instructions do not assure application technological properties of the product.

8